


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| D1 | 23.6 |
| D2 | 12.2 |
| D3 | 15.9 |
| D4 | 18.3 |
| E | 0.23 |
| K | 3.89 |
| L1 | 35 |
| L2 | 15.8 |
| L3 | 12.2 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|---|
| 1 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 2 | ISOLIERKÖRPER MITTE / WAYER |
| 4 | DICHTKÖRPER / GROMMET |
| 5 | ENDRING / ENDRING |
| 7 | KONTAKT BUCHSE / CONTACT SOCKET |
| 8 | GEHÄUSE / RECEPTACLE |
| 12 | ÜBERWURFMUTTER / COUPLING NUT |
| 14 | WELLFEDER / WASHER |
| 17 | ADAPTER / ADAPTER |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.

Specification and Dimensions subject to change
Drawings illustrate normal insulator positioning

Material Specification:

Shell Material: Aluminium alloy

Shell Plating: Zinc cobalt, black

Insulator Material: Polychloroprene

Contact Material: Copper alloy

Contact Plating: #12/16:gold plated, #20:contact area gold plated

all dimensions are in mm
Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for
CUSTOMER



Engineered for life
ITT CANNON GmbH
D - 71384 Weinstadt/Germany

description
KPSE6E10-6S-DN-A232
Straight plug
Shrink boot adapter
Crimp Contacts / Socket / Layout: 10-6

© All rights reserved. Reproduction or issue to third in any form
whenever is only permitted with written authorization of ITT Cannon



page
1/1

revision
4152 30. Apr 24