


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 28.5 |
| B | 23 |
| C | 3.2 |
| D1 | 22.23 |
| D2 | 20.5 |
| E | 0.46 |
| K | 3.89 |
| L1 | 21.1 |
| L2 | 11.6 |
| L3 | 1.9 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|---|
| 2 | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3 | DICHTRING / GASKET |
| 7 | KONTAKT BUCHSE / CONTACT SOCKET |
| 8 | GEHÄUSE / RECEPTACLE |
| 19 | BAYONETTSTIFT / BAYONET PIN |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Specification and Dimensions subject to change
 Drawings illustrate normal insulator positioning

| Material Specification: | |
|-------------------------|--|
| Shell Material: | Aluminium alloy |
| Shell Plating: | Nickel |
| Insulator Material: | Polychloroprene |
| Contact Material: | Copper alloy |
| Contact Plating: | #12/16:gold plated, #20:contact area gold plated |

all dimensions are in mm
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for
 CUSTOMER



Engineered for life
 ITT CANNON GmbH
 D - 71384 Weinstadt/Germany

description KPT2E14-19S-A34
 Box mounting receptacle

Solder Cup / Socket / Layout: 14-19

