

61 PC-Kontaktbohrungen Ø1±0,1

Ansicht ist auf der Steckseite Stift-Stecker gezeichnet.

Fuer Steckseite Buchsen-Stecker ist das Bohrild spiegelbildlich zur Hauptachse (▼)

Fuer Winkelverdrehung sind die Koordinaten entsprechend umzurechnen

61 PC-contact holes Ø1±0,1

View on mating face of pin-connector

For mating face of socket-connector the hole pattern is symetrically to the main axis (▼)


For angular rotation the coordinates must be changed accordingly

Winkelverdrehung: W = 90°

angular rotations: X = 180°

Y = 270°

Z = 324°



Bohrung hole	Lage / position		Bohrung hole	Lage / position		Bohrung hole	Lage / position		Bohrung hole	Lage / position	
	X-Achse ±0,05	Y-Achse ±0,05		X-Achse ±0,05	Y-Achse ±0,05		X-Achse ±0,05	Y-Achse ±0,05		X-Achse ±0,05	Y-Achse ±0,05
A	4,98	12,7	T	-12,98	-4,17	j	3,38	-9,63	BB	0	-6,78
B	7,98	11,05	U	-13,61	-0,76	k	0	-10,21	CC	-3,33	-5,92
C	10,49	8,71	V	-13,39	2,57	m	-3,38	-9,63	DD	-5,79	-3,53
D	12,32	5,84	W	-12,32	5,84	n	-6,38	-7,98	EE	-6,78	-0,25
E	13,39	2,57	X	-10,49	8,71	p	-8,66	-5,41	FF	-6,02	3,1
F	13,61	-0,76	Y	-7,98	11,05	q	-9,96	-2,24	GG	-3,73	5,66
G	12,98	-4,17	Z	-4,98	12,7	r	-10,13	1,17	HH	0	5,08
H	11,53	-7,29	a	-1,73	11,53	s	-9,19	4,45	JJ	2,67	2,39
J	9,35	-9,93	b	1,73	11,53	t	-7,24	7,19	KK	3,43	-1,04
K	6,58	-11,94	c	4,39	9,22	u	-4,39	9,22	LL	0	-3,35
L	3,4	-13,18	d	7,24	7,19	v	0	8,59	MM	-3,43	-1,04
M	0	-13,64	e	9,19	4,45	w	3,73	5,66	NN	-2,67	2,39
N	-3,4	-13,18	f	10,13	1,17	x	6,02	3,1	PP	0	0
P	-6,58	-11,94	g	9,96	-2,24	y	6,78	-0,25			
R	-9,35	-9,93	h	8,66	-5,41	z	5,79	-3,53			
S	-11,53	-7,29	i	6,38	-7,98	AA	3,33	-5,92			

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
Specification and Dimensions subject to change
Drawings illustrate normal insulator positioning

Material Specification:
Shell Material: Aluminium alloy
Shell Plating: Olive drab chromate over cadmium plating
Insulator Material: Polychloroprene
Contact Material: Copper alloy
Contact Plating: gold plated

all dimensions are in mm
Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for
CUSTOMER



description KPT2E24-61P-EW
Box mounting receptacle

Solder Pin 0.6 x 7 mm / Pin / Layout: 24-61

© All rights reserved. Reproduction or issue to third in any form
whatever is only permitted with written authorization of ITT Cannon



page 2/2
revision 4153 30. Apr 24