


NO.	MASSE / DIMENSION
A	30.3
B	35.4
C	23.9
D1	1-20UNEF-2A
D2	22.23
D3	38.1
D4	0.6
E	8.25
K	2.16
L1	17.7
L2	3.2

NO.	BESCHREIBUNG / DESCRIPTION
1	ISOLIERKÖRPER STIFT / INSULATOR PIN
3	DICHTRING / GASKET
6	KONTAKT STIFT / CONTACT PIN
8	GEHÄUSE / RECEPTACLE
10	O-RING / O-RING
11	SECHSKANTMUTTER / HEX NUT
19	BAYONETTSTIFT / BAYONET PIN



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.

Specification and Dimensions subject to change  
Drawings illustrate normal insulator positioning

**Material Specification:**

Shell Material: Aluminium alloy  
Shell Plating: Nickel  
Insulator Material: Polychloroprene  
Contact Material: Copper alloy  
Contact Plating: gold plated

all dimensions are in mm

Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for  
**CUSTOMER**



description **KPT7A14-19P-EW-A34**  
Jam nut receptacle  
General duty  
Solder Pin 0.6 x 7 mm / Pin / Layout: 14-19

© All rights reserved. Reproduction or issue to third in any form  
whenever is only permitted with written authorization of ITT Cannon



page 1/2 revision 4153 30. Apr 24