



Datasheet for part number M83513/25-C02NN

| |
|---|
| Our Catalog Part Number: M83513/25-C02NN |
| Our Global Manufacturing Part Number: 154173-0058 MS |
| Brand: Cannon Product Category: Micro Product Line: Micros Series: M83513-10-27 |

| Product Datasheet | |
|---------------------------------|--|
| Series | Micro D Metal Shell - 0.050 inch spacing |
| Slash Sheet | Connector, Receptacle, BS, Sizes 9 – 37 |
| Arrangement | 21 Contact |
| Contact Typ | soldert pot |
| Contact Material | gold plated copper alloy |
| Contact Resistance | 8 milliohms max. |
| Wire Length | 0.140" long, #24 AWG solid copper wire per QQ-W-343, Type "S", solder dipped |
| Shell Material | Aluminum |
| Shell Finish | Electroless Nickel |
| Insulator | LCP |
| Hardware | No jackpost |
| Current Rating | 3 A max. |
| Dielectric Withstanding Voltage | 600 VAC at sea level 150 VAC at 70,00' altitude |
| Insulator Resistance | 5000 megohms min. |
| Thermal Shock | -55°/+125° |
| Physical Shock | 50 G's, 3 axes, 6 milisecond duration sawtooth pulse |
| Vibration | 20G's, 10-2000 Hz. 12 hours |
| Durability | 500 cycles of mating and unmating, 500 CPH max. |
| Moisture Resistance | Insulator resistance > 100 megohms |
| SaltSpray | 48 hours |