


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| D1 | 30.1 |
| D2 | 18.2 |
| D3 | 15.45 |
| D4 | 22.2 |
| D5 | 25 |
| E | 8.02 |
| K | 2.16 |
| L1 | 49 |
| L2 | 21.4 |
| L3 | 18 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|--|
| 1 | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 2 | ISOLIERKÖRPER MITTE / WAYER |
| 4 | DICKTKÖRPER / GROMMET |
| 6 | KONTAKT STIFT / CONTACT PIN |
| 8 | GEHÄUSE / RECEPTACLE |
| 12 | ÜBERWURFMUTTER / COUPLING NUT |
| 13 | ÜBERWURFMUTTER F. ENDGEH. / COUPLING NUT |
| 14 | WELLFEDER / WASHER |
| 17 | ADAPTER / ADAPTER |
| 18 | KLEMM-MUTTER / CLAMP NUT |
| 21 | DRAHT / FIXING WIRE |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Specification and Dimensions subject to change
 Drawings illustrate normal insulator positioning

| |
|-------------------------------------|
| Material Specification: |
| Shell Material: Aluminium alloy |
| Shell Plating: Zinc cobalt, green |
| Insulator Material: Polychloroprene |
| Contact Material: Copper alloy |
| Contact Plating: gold plated |

all dimensions are in mm
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m
 drawing for CUSTOMER

ITT
Engineered for life
 ITT CANNON GmbH
 D - 71384 Weinstadt/Germany

description **KPSE6E14-19P-DZ-A233**
Straight plug
 Endbell for shielding braids and shrink boots
 Crimp Contacts / Pin / Layout: 14-19