



Datasheet for part number MDSM-30PE-Z33-VR22

| |
|---|
| Our Catalog Part Number: MDSM-30PE-Z33-VR22 |
| Our Global Manufacturing Part Number: 121661-1137 |
| Brand: Cannon Product Category: Micro Product Line: Micros Series: MDSM |

| Product Datasheet | |
|--------------------------|--|
| Series | Micro MDSM |
| Mating Cycles | 500 |
| Layout | 30 contacts |
| Gender | Pin |
| Termination Type | Solder pin 90°, spacing 1,27 x 2,54 mm, with rivet nut and grounding tab |
| Mounting Methode | Locking screw, short |
| Packaging | 22 pieces in tube packaging |
| Insulator | Thermoplast, UL94V-0 |
| Contact guiding plate | PA, high temperature resistant |
| Shell | Steel, tinned and nickel plated |
| Contact Type | Copper alloy |
| Contact Finish | Gold over PdNi |
| Contact Termination Area | Tin |
| Wire size | AWG 26 - 28 |
| Insulation diameter | 0.95 mm max |
| Contact spacing | 1.27 mm |
| Temperature range | -55°/+125° |
| Current rating | 2.5 A / 25°C (row 1, 2) 1.8 A / 25°C (row 3, 4) |
| Test voltage | 350 Vrms |
| Contact resistance | 35 mOhm max (row 1, 2) 55 mOhm max (row 3, 4) |
| Insulation resistance | 500 mOhm min |